

Dell Fibre Channel Card



AI Overview

Dell Fibre Channel cards are high-performance Host Bus Adapters (HBAs) designed for secure, low-latency storage connectivity in Dell servers. Overview Dell Fibre Channel (FC) cards, also known as Host Bus Adapters (HBAs), are used to connect servers to Storage Area Networks (SANs), providing high-speed, reliable data transfer. These cards support PCIe slots and are compatible with various Dell PowerEdge servers, including the 2950 and R740 models. They enable fast communication between servers and storage arrays, supporting both SCSI FC and NVMe over FC protocols.

Key Features

- High Performance:** Dell FC HBAs offer low latency and high throughput, with some models supporting over 10 million IOPS and improved application response times compared to previous generations.
- Security:** Advanced models, such as Emulex SecureHBAs, provide in-flight data encryption (EDIF) and integrate post-quantum cryptography (PQC) to protect sensitive data against emerging threats.
- Manageability:** These cards support centralized management tools like Emulex HBA Manager and SAN Manager 2, allowing administrators to monitor performance, troubleshoot issues, and update firmware without server downtime.
- Compatibility:** Dell FC cards are available for multiple server generations. For example, the PowerEdge 2950 supports up to three PCIe or two PCI-X HBAs depending on riser configuration, while the R740 supports PCIe FC cards with low-profile or full-height variations.
- Advanced Features:** Many Dell FC HBAs support Fabric Vision features, including congestion visualization, adaptive congestion management, and diagnostics like FC Trace Route and FC Ping.

Installation and Considerations

- Slot Requirements:** Ensure the server has available PCIe slots compatible with the card's form factor (low-profile or full-height) and speed requirements.
- Cabling:** Fibre Channel cables are sold separately and must match the card's interface type (SFP, SFP+, or QSFP variants) for proper connectivity.
- Server S...**

Article Content

QLE2690/2690L-DEL and QLE2692/2692L-DEL Data Sheet

QLE2690/2690L-DEL and QLE2692/2692L-DEL Single and Dual-port 16Gb Fibre Channel Adapters The latest and most advanced 16Gb Fibre Channel HBA from QLogic, available in single and dual-port

QLogic QLE2772 Dual-Port FC32 Fiber Channel PCIe

Form Factor: PCIe adapter Network Card Brand & Model: Dell QLogic QLE2772 Ports and Speed: 2xFC32 Interface: Fiber Channel Dell Server 14th Gen

Dell PowerEdge R470 Rack Server

The Dell PowerEdge R470 is a 1U, one-socket rack server with purpose-built solution for maximum energy efficiency and cost-effectiveness in diverse and expansive data landscapes

Canonical LXD 6.9 Adds Dell PowerStore Driver and Fibre Channel

Canonical has released LXD 6.9 with updates aimed squarely at storage teams: a native driver for Dell PowerStore arrays, a new Fibre Channel connector for remote storage generally, and support for

Dell PowerEdge R770 Rack Server

Discover the Dell PowerEdge R770, a powerful server with advanced processing, scalable storage, and robust security.

Dell DTV7K / Silicom PE310F4I71LB-XR Quad Port

Dell DTV7K / Silicom PE310F4I71LB-XR Quad Port 10GB FC Fiber Channel, Full Height Network Card / Server Adapter - New Pull

Support For Dell Laptop Computers, Desktops, Printers,

Automated network fabric performance optimization (FPIN): PowerMax quickly identifies Fibre Channel network congestion (slow drain) and isolates root cause

Emulex LPE1205-M 8Gbps Fibre Channel Card for M1000E-Series ...

The Emulex LPE1205-M Fiber-Channel Card from Dell™ facilitates optimization of internal links for improved high-speed performance for your Server. Its LightPulse Virtual HBA technology provides

DELL 0C856M Emulex LPE12002 8GB Dual Port PCIe

DELL 0C856M Emulex LPE12002 8GB Dual Port PCIe Fibre Channel Card C856M mit 2x GBIC

Dell QLE2690-DELL 16Gb 1-Port PCIe3 X8 Full Height

DELL 16gb Single Port Pci Express 3.0 X8 Fibre Channel Host Bus Adapter With Product Brief 8G Fibre Channel Mezzanine Card for Dell

Streamlined installation and management, unrivaled scalability, and industry-leading virtualization support makes the Emulex LPe1205-M dual-channel mezzanine card by Broadcom an ideal solution

Windows drivers for Marvell QLogic Fibre Channel adapters

This software bundle includes the Dell Update Package with Windows Drivers for Marvell adapters.

Fibre Channel HBAs | Dell USA

Add the products you would like to compare, and quickly determine which is best for your needs.

Fibre-Channel-HBAs | Dell Deutschland

Entdecken Sie unsere Angebote auf Mäuse, Tastaturen, Taschen und anderem PC-Zubehör. Fügen Sie Produkte hinzu, die Sie vergleichen möchten, um schnell festzustellen, welches sich am besten für

DELL Dual Port SFP+ 16Gbit/s card | Servershop24

DELL QLE2662-DEL Dual Port 16G SFP+ Fibre Channel Host Bus Adapter / FC

Dell QLogic 2692 Dual Port 16GbE Fibre Channel HBA, PCIe Full

Dell QLogic 2692 Dual Port 16GbE Fibre Channel HBA, PCIe Full Height, V2 - PCIe - 2 x Total Fibre Channel Port (s) - Plug-in Card - 540-BDHW The Qlogic 2692 Host Bus Adapter from Dell [™] offers

Emulex SecureHBA Fibre Channel Adapters Product Brief

The Emulex® Secure Fibre Channel (FC) host bus adapters (HBAs) by Broadcom are designed to deliver the highest level of security, performance, and manageability for mission-critical infrastructures.

PowerEdge R7725 | Dell USA

Dell PowerEdge R7725 is a 2U dual-socket rack server providing exceptional performance and flexibility with multiple configuration options

Dell PowerEdge R910 Fiber Channel (HBA) Cards

Genuine Dell fibre channel (HBA) cards and converged network adapters. Tested and backed by our 90-day warranty.

Dell PowerEdge 2950 Fibre Channel Host Bus Adapter Cards (HBA)

Genuine Dell Fibre Channel Host Bus Adapter Cards (HBA) for PowerEdge 2950 servers. Refurbished, tested and pulled from working machines. 90-day parts replacement warranty.

Dell PowerStore: Best Practices Guide

Fibre Channel fabrics For Fibre Channel connectivity, configure dual redundant fabrics, with each PowerStore node and each external host having connectivity on each of the fabrics. Minimize the

Dell TCK3G QLogic QLE2692L HBA 16GB FC Dual

DELL TCK3G Qlogic Qle2692l Hba 16gb Fc Dual Port Sfp Pci-e 3.0 X8 Host Bus

QLogic User's Guide for Fibre Channel Adapter, Converged Network ...

QLogic Fibre Channel Adapter, Converged Network Adapter and Intelligent Ethernet Adapters user guide Fibre Channel Supported Products QLE2560 FC8 Single Channel HBA

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.sky-connect.co.za>

Email: info@sky-connect.co.za

Phone: +44 20 7946 0958

Address: 1 Cornhill, London EC3V 3ND, United Kingdom

This document is for informational purposes only. Specifications subject to change without notice.

